



Telecommunications equipment – Leased Lines – Technical requirements for connection – Amendment 1

*Telekommunikationsutrustning – Hyrda ledningar – Tekniska krav för anslutning –
Tillägg 1*

1 Introduction

This amendment refers to Edition 3 of SS 63 63 40. Clause 2 ("Amendments to 8211-A 113") of that document shall be replaced by clause 2 below.

2 Amendments

Subclause 5.2 At the end of the first sentence shall be added "or of the type RJ 11/12".

Subclause 5.3.2.1 The text shall be amended to read in full:

"DC as well as peak values of DC pulses and rms values of AC with a frequency up to 50 Hz, shall not exceed 60 V, corresponding to +38 dBu. However, a ringing signal is permitted to reach 80 V.

The rms value of the current shall not exceed 40 mA during normal operation or when the line is shortcircuited"

Figure 1 A point AA defined by the pair of values 50 Hz and +36 dBu shall be inserted in the figure and the included table.

Subclause 5.3.2.3 "3 400" shall be replaced by "3 900" in the heading and the text.

Subclause 5.3.2.4 "3 400" shall be replaced by "3 900" in the heading and the text.

Subclause 5.3.2.7 "3 400" shall be replaced by "3 900" in the 5th paragraph.

Subclause 5.3.2.7 "3.4" shall be replaced by "3.9" in the last paragraph.

Figure 2 The pair of values defining point A in the figure and the included table shall be changed to -33 dBm at 3,9 kHz.

- Subclause 5.3.5** The first paragraph shall be amended to read:
”The return loss between the equipment’s impedance and a complex reference impedance made up of 270 Ω in series with a parallel combination of 750 Ω and 150 nF, shall be at least 6 dB in the 200 – 3 800 Hz frequency band.”
The third paragraph shall be deleted.
The last sentence and figure 3 shall be deleted.
- Subclause 5.3.7** The subclause shall be deleted.
- Subclause 5.4.1** The test shall be amended to read in full:
”5.4.1 Safety
There are no safety requirements under this Swedish standard.
NOTE – Safety requirements are imposed under Directive 73/23/EEC and articles 5(a) and 5(b) of Directive 98/13/EC.”
NOTE – From 8th April 2000, safety requirements are imposed under articles 3.1(a) and 3.1(b) of Directive 99/5/EC.
- Subclause 5.4.3** The subclause shall be deleted.
- Clause 6** The clause shall be deleted.